


FOAM FILL - CONTINUOUSLY
AND COMPLETELY ALL
RIDGE JOINTS

SIPTP SCREW (W/ WASHER) 1 1/2"
LONGER THAN PANEL THICKNESS
SEE ENGINEERING DATA FOR
SPACING REQUIREMENTS



SEAL ROOF RIDGE WITH
PLIABLE ROOF MEMBRANE
EXTENDING 6" TO EACH
SIDE OF THE APEX

CONSTRUCTION SEALANT, 1/4"
BEAD-CONTINUOUS WOOD-TO-
WOOD CONNECTIONS TYP.

2X LUMBER WEDGES
SHAPED TO FILL
VOID ABOVE BEAM

1 1/2" MINIMUM BEARING PER
PANEL AT SUPPORT POINT

ALL FASTENERS SHOWN ARE MINIMUM REQUIREMENTS AND MAY BE CHANGED BY THE ENGINEER OF RECORD TO MEET DESIGN REQUIREMENTS.

UNLESS OTHERWISE NOTED, ANY AND ALL LUMBER AND ENGINEERED LUMBER TO BE PROVIDED BY OTHERS.

CONSTRUCTION DETAILS MAY SHOW ITEMS THAT ARE NOT SUPPLIED BY PORTERCORP. FASTENING OF MATERIALS NOT SUPPLIED BY PORTERCORP IS THE RESPONSIBILITY OF THE INSTALLER. PLEASE CONTACT YOUR SALES REPRESENTATIVE IF YOU HAVE ANY QUESTIONS ABOUT YOUR ORDER.

SIP INSTALLER IS RESPONSIBLE FOR THE PROPER INSTALLATION OF PANELS. THIS IS AN ENGINEERED SYSTEM. FAILURE TO FOLLOW ALL CONSTRUCTION DETAILS AND INFORMATION IN FASTENER SCHEDULE WILL VOID THE PORTERSIP WARRANTY. PLEASE CONTACT PORTERCORP WITH ANY QUESTIONS.

SIP TAPE IS APPLIED TO THE PREDOMINANTLY WARMN SIDE OF THE JOINT. INSIDE IN NORTHERN, COLDER CLIMATES; OUTSIDE IN SOUTHERN, WARMER CLIMATES.

PORTERcorp

Manufacturers of PorterSIPs®

4240 N. 136th Ave phone. 616.399.1963
Holland, MI 49424 fax. 616.928.0076

R-17

ROOF RIDGE CONNECTION
WITHOUT SOLID BLOCKING

CONFIDENTIAL DRAWING INFORMATION CONTAINED HEREIN IS THE PROPERTY OF PORTERCORP. DRAWING IS NOT TO BE COPIED OR DISCLOSED TO OTHERS WITHOUT THE CONSENT OF PORTERCORP.